

- Ø100 - Ø315 mm aralığında 6 farklı çap
- Kolay ve hızlı montaj ile yer ve işçilikten tasarruf
- Yüksek basınç ve verim sağlayan geriye eğik radyal kanatlar
- Nemli ortamlarda çalışma imkanı, IP 44 koruma sınıfı (Elektrik bağlantı kutusu IP 54)
- Otomatik termik korumalı, dıştan rotorlu, bakım gerektirmeyen rulmanlı, tek fazlı motor
- % 0 - % 100 kapasite aralığında hız kontrolü yapabilme imkanı

- 6 different diameters in the range of 100-315 mm
- Easy and quick installation
- Backward curved centrifugal blades providing high pressure and efficiency
- The opportunity to work in humid environments, motor protection class is IP 44 and electrical connection box protection class is IP 54
- Single phased motor with automatically activated thermic protection, external rotor and maintenance-free bearings
- Speed controllers are optional to control the capacity in the range of % 0 - %100.

VENCO MODEL	Akım Current (A)	Güç Power (W)	Devir Revolution (rpm)	Maks. Sic. Max. Temp. (°C)	Ses Seviyesi Sound Level dB(A)@3m	Ağırlık Weight (kg)	Ød	ØD	a	b	c	e	Hız Anahtarı Speed Controller
KV 100A	0.18	41	1.730	80	36	2.5	100	240	310	295	111	24	VSC 1
KV 125C	0.27	62	2.320	70	43	2.5	125	240	310	295	111	24	VSC 1
KV 160C	0.44	100	2.480	65	50	4.0	160	342	400	385	128	26	VSC 1
KV 200A	0.5	115	2.580	60	47	4.1	200	342	400	385	127	34	VSC 1
KV 200B	0.69	158	2.500	60	49	4.8	200	342	400	385	127	34	VSC 1
KV 315B	0.84	190	2.465	50	48	5.6	315	400	460	445	158	34	VSC 1
KV 315C	1.19	274	2.500	50	51	6.0	315	400	460	445	158	34	VSC 1

Statik (Pa) Static (Pa)	HAVA DEBİSİ (m³/h) / AIR FLOW						
	KV 100A	KV 125C	KV 160C	KV 200A	KV 200B	KV 315B	KV 315C
0	309	448	865	925	1063	1775	1775
50	245	390	791	840	1004	1647	1647
100	191	330	712	750	939	1520	1520
125	166	300	670	702	905	1457	1457
150	143	269	626	653	868	1394	1394
175	121	237	581	601	829	1326	1326
200	99	205	532	546	788	1263	1263
225	79	172	481	489	745	1200	1200
250	59	139	427	428	698	1137	1137
275	40	105	368	363	650	1074	1074
300			305	292	598	1011	1011
325			234	214	545	950	950
350			153	126	489	887	887
375			55	24	430	825	825
400					370	763	763
450					250	641	641
500					137	519	519
550					37	398	398
600						278	278
650						159	159

